



European Geosciences Union General Assembly 2015, EGU

Division Energy, Resources & Environment, ERE

Hydro-mechanical simulations of well abandonment at the Ketzin pilot site for CO₂ storage verify wellbore system integrity

Victoria Unger^{a,b}, Thomas Kempka^{a,*}

^aGFZ German Research Centre for Geosciences, Section 5.3 – Hydrogeology, Telegrafenberg, 14473 Potsdam, Germany

^bInstitute of Earth and Environmental Science, University of Potsdam, Karl-Liebknecht-Str. 24-25, 14476 Potsdam, Germany

Abstract

In geological underground utilization, operating and abandoned wells have been identified as main potential leakage pathways for reservoir fluids. In the scope of the well abandonment procedure currently carried out at the Ketzin pilot site for CO₂ storage in Germany, we implemented a hydro-mechanical wellbore model to assess the integrity of the entire wellbore system. Thereto, we investigated the impacts of stress changes associated with site operation and abandonment, including the final casing removal and cement backfill to be undertaken for well abandonment. Simulation results show a high unlikelihood of potential formation of fluid leakage pathways in the wellbore system.

© 2015 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

Peer-review under responsibility of the GFZ German Research Centre for Geosciences

Keywords: Well integrity; well abandonment; CO₂ storage; hydro-mechanical modeling; numerical simulation

* Corresponding author. Tel.: +49-331-288-1865.
E-mail address: kempka@gfz-potsdam.de

1. Introduction

1.1. CO₂ storage at the Ketzin pilot site, Germany

The Ketzin pilot site for CO₂ storage is located near Berlin in the Federal State of Brandenburg, Germany. During the injection period from June 2008 to August 2013, 67 kt CO₂ were stored in the Stuttgart Formation formed by sandstone channels of fluvial origin at 630 m - 650 m depth, embedded in a floodplain facies with a total thickness of about 74 m [1, 2]. A multi-barrier system of several caprock units as well as the Ketzin anticline ensure structural trapping of gaseous CO₂. Beside the combined injection and observation well Ktzi 201, four additional wells (Ktzi 200, Ktzi 202, Ktzi 203, P300) were drilled to monitor CO₂ migration as well as reservoir and caprock integrity. Site-specific research activities at the Ketzin pilot site have been accomplished by 18 German and European projects so far and comprise of operational data acquisition, monitoring and modelling [3-6]. Long-term stabilization assessments for the post-operational phase were carried out by coupled numerical modeling [7-11], but numerical simulations on well integrity during site operation and well abandonment were not established so far.

1.2. Wellbore systems as potential leakage pathways

Wellbore systems are addressed as the main potential leakage pathways for CO₂ involving different leakage mechanisms [12-18]. In this regard, the cement-casing and cement-rock interfaces, which are suspect to stress changes and corrosion, are mainly emphasized for consideration in well integrity studies [19-21]. Stress changes are generally occurring during site operation, but also as a result of post-operational CO₂ migration, inducing spatial pore pressure changes within the reservoir. In this work, we focus on the impacts of stress changes at the Ktzi 201 injection well occurring during CO₂ injection in the operational phase and cement backfilling in the abandonment phase [22-24].

2. Model setup and parameterization

2.1. 3D model of the entire wellbore system

The implemented 3D model considers eleven geological formations from the Triassic to Quaternary including the major fluvial sandstone channels within the Stuttgart Formation at 630 m - 650 m depth [2, 25]. Based on site operation reports [26], we integrated all wellbore system components such as cement sheaths, steel casings, tubing and packer elements as well as wellbore annuli for a detailed representation of the entire wellbore system (Fig. 1a).




Fig. 1. (a) 3D hydro-mechanical model of the entire wellbore system, including casings, cement sheaths and tubing and all considered formations (not to scale); (b) Vertical cement-casing and cement-rock interfaces (not to scale).

The numerical model grid has a horizontal discretization of 5 m x 5 m to focus on near wellbore region, whereby element size increases with increasing distance from the wellbore. A tartan grid is used for vertical discretization over the entire model thickness of 1,500 m to ensure a sufficient resolution of all wellbore system elements as well as of the reservoir unit in the numerical model. At the vertical cement-casing and cement-rock interfaces, we added 21 numerical interfaces to observe normal and shear displacements during the simulation runs (Fig. 1b). The total number of elements used in the coupled hydro-mechanical model amounts to about 250,000.

2.2. Mechanical parameters

Geomechanical parameters assigned to the geological formations were derived from log-data [3, 27] and operational reports [25, 26], while well system parameterization was undertaken based on different sources [17, 28, 29]. The formations and cement sheaths were parameterized using a plastoelastic constitutive law, whereas the casing, tubing and packer elements were assumed to behave linear elastic. Tables 1 and 2 show the parameters that were assigned to the model, including density, Young's modulus, Poisson's coefficient, friction angle and uniaxial compressive strength.

Table 1. Mechanical parameters assigned to the geological formations implemented in the hydro-mechanical model.

Formation	Young's modulus E (GPa)	Poisson's coefficient ν (-)	Friction angle ϕ (°)	UCS C_0 (MPa)	Density ρ (kg/m ³)
Quaternary	3.11	0.48	35.16	4.97	2,100
Rupelian	3.24	0.46	29.79	5.95	2,200
Pliensbachian	3.83	0.43	25.59	10.01	2,275
Sinemurian	3.78	0.41	25.77	11.54	2,314
Hettangian	4.45	0.42	29.48	12.68	2,198
Exter	5.07	0.37	26.16	17.80	2,250
Arnstadt	6.86	0.31	25.65	27.82	2,428
Weser	8.00	0.31	28.03	34.35	2,579
Stuttgart (floodplain facies)	7.83	0.35	29.57	36.73	2,464
Stuttgart (sandstone channels)	11.61	0.36	34.75	47.53	2,280
Grabfeld	6.12	0.34	26.96	29.88	2,508

Table 2. Mechanical parameters assigned to the wellbore system.

Elements	Young's modulus E (GPa)	Poisson's coefficient ν (-)	Friction angle ϕ (°)	Cohesion c (MPa)	Density ρ (g/m ³)
Class G cement	8.3	0.10	17.10	2.60	1,850
EverCRETE cement	11	0.17	17.10	2.60	1,917
Casing / Tubing	210	0.30			7,800
Packer	0.006	0.48			1,100

Parameters not available in the references, such as the cohesion c and the tensile strength T_0 were calculated by the Equations 1 and 2 referred to Jaeger et al. [30], where μ is equal to $\tan(\phi)$, known as the coefficient of internal friction, and C_0 the uniaxial compressive strength (UCS).

$$c = \frac{1}{2} \frac{C_0}{(1 + \mu^2)^{1/2} + \mu} \quad (1)$$

$$T_0 = \frac{C_0}{10} \quad (2)$$

The numerical interfaces were implemented and parametrized as described in [31] with a friction angle of 26.6° for cement-rock interfaces and 16.6° for cement-casing interfaces according to Topini et al. [32]. The required normal and shear stiffnesses (k_n and k_s) were assumed to be equal and expressed as the tenfold of the maximum stiffness of the adjacent materials. Bulk- (G) and shear moduli (K) were referred to the softer material with Δz_{\min} representing the width of the smallest adjacent zone in Equation 3.

$$k_s = k_n = 10 \cdot \frac{K + \frac{4}{3}G}{\Delta z_{\min}} \quad (3)$$

2.3. Boundary and initial conditions

We assigned constant velocities of zero perpendicular to the lateral and bottom model boundaries, while the upper boundary was allowed to displace in any direction (Fig. 2). The normal faulting stress regime identified for the Ketzin pilot site was implemented by applying an initial stress regime with a horizontal to vertical total stress ratio of 0.85 and equal horizontal principal stresses [27]. A hydrostatic pressure gradient of 1×10^{-4} Pa/m was applied based on well log data [26].




Fig. 2. 2D view of the hydro-mechanical model and its boundary conditions applied at the lateral and bottom model boundaries. The model setup considers eleven formations including the reservoir sandstone channels and floodplain facies within the Stuttgart Formation.

2.4. Simulation steps

The hydro-mechanical calculations were carried out in three simulation steps:

- Calculation of hydro-mechanical equilibrium prior to any CO₂ injection
- Simulation of operational phase based on available injection and post-injection bottomhole pressure data
- Simulation of abandonment phase using two backfilling steps

The first hydro-mechanical equilibrium computation considered the geological system before drilling any wells. After the implementation of the Ktzi 201 wellbore system with the numerical interfaces, a second hydro-mechanical equilibrium run was carried out. To simulate the operational phase, we selected 30 representative time steps from the observed Ktzi 201 bottomhole pressure for integration of the injection and post-injection phases at the Ketzin pilot site into the hydro-mechanical model (Fig. 3). Observed pressure and temperature data for each time step were derived from Moeller et al. [4]. A dynamic calculation of the CO₂ density was employed as a function of pressure and temperature to determine all required fluid pressures over the entire well length and reservoir depth using the Span and Wagner equation of state [33]. The bottomhole pressure determined in January 2015 was considered as reference pressure for the abandonment phase.




Fig. 3. Observed Ktzi 201 well bottomhole pressure at 550 m depth (blue line) from June 2008 to January 2015 [m]. Data selected as input for the hydro-mechanical simulations are marked by red squares..

The abandonment phase of the Ketzin pilot site wells is scheduled to be carried out in two steps (Fig. 4). After removing the tubing and casings located in front of any open well annulus, the lower 214 m of the borehole will be filled with Schlumberger EverCRETE cement. The second step considers backfilling of the remaining open borehole with a Class G cement up to the ground surface.




Fig. 4. 3D view of the two simulation steps representing the well abandonment phase: backfill with Schlumberger EverCRETE (blue) and Class G cements (green).

3. Results

Our simulation results demonstrate that the formation of potential fluid leakage pathways in the wellbore system is highly unlikely. Mechanical failure of casing or cement sheaths does not occur at any time of the simulation. Maximum shear displacements at the cement-casing and cement-rock interfaces are below 0.5 mm, and thus negligible in terms of shear fracture formation (Fig. 5a). Maximum interface normal displacements are compressive and below 0.005 mm, so that tensile fracturing cannot occur (Fig. 5b).




Fig. 5. Numerical simulation results demonstrate that relevant interface (a) shear displacements are only observed at the depth of the filter screen, while (b) relevant normal displacements are generally compressive and occur only between the inner casing and backfill cement (not to scale).

4. Conclusions

Our simulation results indicate that failure of the Ketzin 201 wellbore system is highly unlikely to occur at the Ketzin pilot site, taking into account the available site-specific data and observations at any time of site operation and well abandonment. Interface normal and shear displacements exhibit such low magnitudes that formation of potential fluid leakage pathways due to hydro-mechanical processes is also highly unlikely. The implemented hydro-mechanical model of the Ketzin 201 wellbore system can be further employed for investigation of different hypothetical failure scenarios and their impact on reactive transport by extending the hydro-mechanical coupling by hydro-chemical processes.

Acknowledgements

The authors gratefully acknowledge the funding for the Ketzin project received from the European Commission (6th and 7th Framework Program), two German ministries - the Federal Ministry of Economics and Technology and the Federal Ministry of Education and Research - and industry since 2004. The ongoing R&D activities are funded within the project COMPLETE by the Federal Ministry of Education and Research. Further funding is received by VGS, RWE, Vattenfall, Statoil, OMV and the Norwegian CLIMIT programme.

References

- [1] Würdemann H, Möller F, Kühn M, Heidug W, Christensen NP, Borm G et al. CO₂SINK - From site characterisation and risk assessment to monitoring and verification: One year of operational experience with the field laboratory for CO₂ storage at Ketzin, Germany. *Int J Greenh Gas Con* 2010; 4(6): 938-951. doi:10.1016/j.ijggc.2010.08.010.
- [2] Norden B, Frykman P. Geological modelling of the Triassic Stuttgart Formation at the Ketzin CO₂ storage site, Germany. *Int J Greenh Gas Con* 2013; 19, 756-774, doi: 10.1016/j.ijggc.2013.04.019.
- [3] Ouellet A, Bérard T, Frykman P, Welsh P, Minton J, Pamucku Y, Hurter S, Schmidt-Hattenberger C. Reservoir geomechanics case study of seal integrity under CO₂ storage conditions at Ketzin, Germany. Ninth Annual Conference on Carbon Capture and Sequestration May 10-13, 2010.
- [4] Möller F, Liebscher A, Martens S, Schmidt-Hattenberger C, Kühn M. Yearly operational datasets of the CO₂ storage pilot site Ketzin, Germany. 2012. In: Scientific technical report: data 12/06; (pii0.2312/GFZ.b103-12066, online only).
- [5] Martens S, Kempka T, Liebscher A, Lüth S, Möller F, Myrntinen A, Norden B, Schmidt-Hattenberger C, Zimmer M, Kühn M, The Ketzin Group. Europe's longest-operating on-shore CO₂ storage site at Ketzin, Germany: A progress report after three years of injection. *Environ Earth Sci* 2012; 67: 323-334. doi: 10.1007/s12665-012-1672-5.
- [6] Martens S, Liebscher A, Möller F, Hennings J, Kempka T, Lüth S, Norden B, Prevedel B, Szizybalski A, Zimmer M, Kühn M, The Ketzin Group. CO₂ Storage at the Ketzin Pilot Site, Germany: Fourth Year of Injection, Monitoring, Modelling and Verification. *Energy Procedia* 2013; 37: 6434-6443. doi:10.1016/j.egypro.2013.06.573.
- [7] Kempka T, Klein E, De Lucia M, Tillner E, Kühn M. Assessment of Long-term CO₂ Trapping Mechanisms at the Ketzin Pilot Site (Germany) by Coupled Numerical Modelling. *Energy Procedia* 2013; 37: 5419-5426. doi: 10.1016/j.egypro.2013.06.460.
- [8] Klein E, De Lucia M, Kempka T, Kühn M. Evaluation of long-term mineral trapping at the Ketzin pilot site for CO₂ storage: An integrative approach using geochemical modelling and reservoir simulation. *Int J Greenh Gas Con* 2013; 19: 720-730. doi:10.1016/j.ijggc.2013.05.014.
- [9] Kempka T, Klapperer S, Norden B. Coupled hydro-mechanical simulations demonstrate system integrity at the Ketzin pilot site for CO₂ storage. *Rock Engineering and Rock Mechanics: Structures in and on Rock-Masses – Proceeding of EUROCK 2014, ISRM European Regional Symposium*, p. 1317-1322.
- [10] Kempka T, De Lucia M, Kühn M. Geomechanical integrity verification and mineral trapping quantification for the Ketzin CO₂ storage pilot site by coupled numerical simulations. *Energy Procedia* 2014; 63: 3330-3338. doi: 10.1016/j.egypro.2014.11.361.
- [11] De Lucia M, Kempka T, Kühn M. A coupling alternative to reactive transport simulations for long-term prediction of chemical reactions in heterogeneous CO₂ storage systems. *Geosci Model Dev* 2015; 8: 279-294. doi: 10.5194/gmd-8-279-2015.
- [12] Celia MA, Bachu S, Nordbotten JM, Gasda S, Dahle HK. Quantitative estimation of CO₂ leakage from geological storage: Analytical models, numerical models, and data needs. In E.S. Rubin, D.W. Keith and C.F. Gilboy (Eds.), *Proceedings of 7th International Conference on Greenhouse Gas Control Technologies 2004*. Volume 1: Peer-Reviewed Papers and Plenary Presentations, IEA Greenhouse Gas Programme, Cheltenham, UK.
- [13] Gasda SE, Nordbotten JM, Celia MA. Determining effective wellbore permeability from a field pressure test: A numerical analysis of detection limits. *Environ Geol* 2008; 54: 1207–1215
- [14] Viswanathan HS, Pawar RJ, Stauffer PH, Kaszuba JP, Carey JW, Olsen SC, Keating GN, Kavetski D, Guthrie GD. Development of a hybrid process and system model for the assessment of wellbore leakage at a geologic CO₂ sequestration site. *Environ Sci Technol* 2008; 42 (19): 7280–7286.

- [15] Nygaard R. Well design and Well Integrity: Wabamun area CO₂ sequestration project (WASP). 2010. Energy and Environmental Systems Group (EES), University of Calgary.
- [16] Crow W, Carey JW, Gasda SE, Williams DB, Celia MA. Wellbore integrity analysis of a natural CO₂ producer. *Int J Greenh Gas Con* 2010; 4: 186–197
- [17] Boulharts H, Cangémi L. D2.3.3 – Report on full scale well modelling and numerical results per site. CO₂CARE – CO₂ Site Closure Assessment Research, Grant Agreement number: 256625, 2011. Online: <http://www.co2care.org>.
- [18] Loizzo M, Akemu OA, Jammes L, Desroches J, Lombardi S, Annunziatellis A. Quantifying the Risk of CO₂ Leakage Through Wellbores. *SPE Drill Complet* 2011; 26(3): 324-31.
- [19] Bachu S, Bennion DB, Experimental assessment of brine and/or CO₂ leakage through well cements at reservoir conditions. *Int J Greenh Gas Con* 2009; 3: 494-501.
- [20] Carey JW, Svec R, Grigg R, Zhang J, Crow W. Experimental investigation of wellbore integrity and CO₂-brine flow along the casing-cement microannulus. *Int J Greenh Gas Con* 2010; 4(2): 272-282.
- [21] Newell DL, Carey JW. Experimental evaluation of wellbore integrity along the cement-rock boundary. *Environ Sci Technol* 2013; 47(1): 276–282.
- [22] Kühn M, Wipki M, Durucan S, Korre A, Deflandre JP, Boulharts H, Lüth S, Frykman P, Wollenweber J, Kronimus A, Chadwick A, Böhm G, The CO₂CARE Group. Key site abandonment steps in CO₂ storage. *Energy Procedia* 2013; 37: 4731-4740. doi: 10.1016/j.egypro.2013.06.382.
- [23] Martens S, Möller F, Streibel M, Liebscher A, The Ketzin Group. Completion of five years of safe CO₂ injection and transition to the post-closure phase at the Ketzin pilot site. *Energy Procedia* 2014; 59: 190-197. doi: 10.1016/j.egypro.2014.10.366.
- [24] Prevedel B, Martens S, Norden B, Henniges J, Freifeld BM. Drilling and abandonment preparation of CO₂ storage wells – Experience from the Ketzin pilot site. *Energy Procedia* 2014; 63: 6067 – 6078. doi: 10.1016/j.egypro.2014.11.639.
- [25] CO₂SINK. Geologischer Abschlussbericht der Bohrung CO₂ Ktzi 201/2007, 2007. Unpublished report.
- [26] CO₂SINK. Bohrtechnischer Abschlussbericht zur Erstellung der Bohrung Ketzin 201 (Ktzi 201), 2007. Unpublished report.
- [27] Sinha BK, Ouellet A, Bérard T. Estimation of principal horizontal stresses using radial profiles of shear slownesses utilizing sonic data from a CO₂ storage site in saline aquifer in Germany. SPWLA 51st Annual Logging Symposium June 19-23, 2010.
- [28] Schlumberger. EverCRETE, Product Sheet, 2007; Online: http://www.slb.com/~media/Files/cementing/product_sheets/evercrete_ps.pdf.
- [29] Barlet-Gouédart V, Rimmelé G, Porcherie O, Quisel N, Desroches J. A solution against well cement degradation under CO₂ geological storage environment. *Int J Greenh Gas Con* 2009; 3(2):206-216.
- [30] Jaeger JC, Cook NGW, Zimmerman RW. *Fundamentals of Rock Mechanics*. Malden, MA: Blackwell Pub, 2007. Print.
- [31] Itasca. FLAC3D Software Version 5.01. User's Manual. Advanced Three-Dimensional Continuum Modelling for Geotechnical Analysis of Rock, Soil and Structural Support. 2013.
- [32] Topini C, Bertolo F, Capasso G, Mantica S. Buckling analysis for long term integrity evaluation of hydrocarbon well. Simulia customer conference, Barcelona, May 17-19, 2011.
- [33] Span R, Wagner W. A new equation of state for carbon dioxide covering the fluid region from the triple-point temperature to 1100 K at pressures up to 800 MPa. *J Phys Chem RefData* 1996; 25(6):206-216.