

Technical Report Profile DEKORP 1984-2S - Reprocessing

(Manfred Stiller & Tatiana Agafonova, GFZ German Research Centre for Geosciences, Potsdam, Germany)

1. Introduction

This is the technical description of new DEKORP 1984-2S seismic reflection data as reprocessed in 2019/20. It builds an addition to the data publication Stiller et al. (2021), which encompasses the first processing of the DEKORP Processing Centre carried out in 1991. The trace data come in SEG Y format, the description of which can be found in the References, SEG Technical Standards: SEG Y rev0 (1975); rev1 (2002).

When using the data please cite:

Homuth, Benjamin; Stiller, Manfred (2022): Reprocessed northern part of deep seismic reflection profile DEKORP 1984-2S across the Taunus Mountains and the Hessian Trough in the state of Hesse, Germany. GFZ Data Services. <https://doi.org/10.5880/GFZ.DEKORP-2S.002>

Licence: Creative Common Attribution 4.0 International (CC BY 4.0)



Table of Contents

1.Introduction	1
2.General	1
2.1.Folder structure DEK84-2S_Rdata	3
3.Seismic Data	3
4.Graphic Data	4
5.Metadata	4
6.References	5
7.Appendix A	6
7.1.Table 1: Field parameter summary and geometry dimensions	6
7.2.Table 2: Reprocessing sequence summary	7

2. General

The folder **DEK84-2S_RData** contains all seismic data and corresponding metadata as well as additional information like e.g. high-resolution graphic representations of the reprocessing results from 2019/20. All data are based on the original field data and on the processing carried out in 1991 at the former DEKORP Processing Centre (DPC) at the Geophysical Institute of the Technical University Clausthal, Germany and have been reprocessed by DMT Petrologic GmbH & Co. KG, Hanover, Germany, supervised by the GFZ Potsdam, Germany (see the corresponding Reprocessing Report and the related FlowCharts coming with the metadata). It is recommended to have also a look at the data publication of the original processing from 1991 (Stiller et al. 2021) which contains a lot of additional information also with respect to the reprocessing results. Other DEKORP profiles can be found in Meissner & Bortfeld (1990) and a basic introduction to the processing of DEKORP data in Stiller & Thomas (1989).

The northernmost 55.64 km of the 250.08 km long profile 2S, i.e. the part located in the State of Hesse, were reprocessed on behalf of the Hessian Agency for Nature Conservation, Environment and Geology. The input data were extended southwards by another 19 km (with decreasing CDP coverage) in order to avoid boundary effects during migration.

All provided SEG Y files are IEEE-32bitFP rev1 with proper binary header. Corresponding downloadable SEG Y format descriptions in PDF can be found in the References, SEG Technical Standards: SEG Y rev0 (1975); rev1 (2002). In the following, as an example, the EBCDIC header for the final pre-stack depth-migrated section is given, containing several useful information. This also supports an easy set-up for the SEG Y input routine of any other software:

SEG-Y Reel Header

C 1 Client: HLNUG, Wiesbaden, Germany
C 2 Contractor: DMT Petrologic GmbH & Co. KG, Hanover, Germany
C 3 Date: 2019-03-22
C 4 Project: 2D Seismic Reprocessing DEKORP, Line DEK84-2S
C 5 Content: CRS Pre-Stack Depth Migration, Filtered and Scaled, Zerophase
C 6 CDP 4586-6253, Sampling Rate: 4m, Length: 70000m
C 7 Polarity: Impedance Increase = Negative Value
C 8 Geodetic Reference: DHDN / 3-Degree Gauss-Kruger Zone 3 (EPSG: 31467)
C 9 Processing Sequence:
C10 1) Data Input
C11 2) Binning and Geometry Load
C12 4) Initial Trace Editing
C13 5) Refraction Statics (Delivered by Client, SRD=400m AMSL)
C14 6) Spherical Divergence Correction (T*VV)
C15 7) 1st Run Surface Consistent Amplitude Balancing
C16 8) Surface Consistent Spiking Deconvolution (160ms, 1.0% Prewhitening, Two
C17 Gates)
C18 9) Bandpass (3Hz-8Hz-80Hz-100Hz)
C19 10) 2nd Run Trace Editing and Surface Consistent Amplitude Balancing
C20 11) Air Blast Attenuation (331m/s)
C21 12) Residual Statics Computation, including Iterative Velocity Updates
C22 13) Noisy Trace Editing (Despike by Standard Deviation) in Supergathers
C23 14) Ground-Roll Suppression in Cone Window
C24 15) CRS Processing
C25 16) Transformation to Zero-Phase
C26 17) Isotropic Kirchhoff Pre-Stack Depth Migration 50 Degree Operator
C27 with iterative Velocityfield Update
C28 18) Residual Moveout Correction, Outer Trace Mute and Stacking
C29 19) Poststack Noise Cleaning: Coherence Enhancement with
C30 F-K Amplitude Power and Time-Variant Scaling
C31 20) SEG-Y Output
C32
C33 Trace Header Byte Positioning: SEG-Standard SEG-Y Rev 1, May 2002
C34 Bin-Center X-Coord 181-184 4I Bin-Center Y-Coord 185-188 4I
C35 Bin-Center X-Coord 73-76 4I Bin-Center Y-Coord 77-80 4I
C36 Bin-Center X-Coord 81-84 4I Bin-Center Y-Coord 85-88 4I
C37 CDP Bin Number 21-24 4I CDP Bin Number 193-196 4I
C38 Bin-Center Elevation 233-236 4I CDP Location Number 237-240 4I
C39 SEG Y REV1
C40 END EBCDIC

2.1. Folder structure DEK84-2S_Rdata

SeismicData	PreStack	ShotGathers_unmigrated	Raw	
		CDPgathers_unmigrated	Preprocessed	
		CRSgathers_unmigrated	Processed	
		ImageGathers_migrated	PreStackTime PreStackDepth	
	PostStack	CRSstacks_unmigrated	Raw	Final
			RMSvelocities	
			PostStack_time-migrated	Raw
		PreStack_time-migrated	IntervalVelocities	
			Raw	Final
		RMSvelocities		
		PreStack_depth-migrated	Raw	Final
			IntervalVelocities	
	VelocityField_unmuted		VelocityField_muted	
	Inversion	Tomography	NodeCount	

GraphicData	FinalStacks
	FinalMigrations
	SeismicAttributes
	Tomography

MetaData	Geometry	Sources
		Receivers
		CDPs
		Relation
SurveyData	Misc	FieldReport
		Maps
		Statics
Misc	Misc	Misc

In a PDF document in the **DEK84-2S_RData** parent folder all files contained in the subfolders are listed together with additional information for a full overview.

3. Seismic Data

The seismic trace data comprise all reprocessed results that are most likely required for further evaluation. They are divided into **PreStack** and **PostStack** data. The reprocessed post-stack data are well suited for getting a structural overview or for reinterpretation of the profile. The reprocessed pre-stack data allow for an application of new stacking or migration methods on raw or pre-processed data.

In the SeismicData/**PreStack** folder there is a set of SGY files, containing the unstacked and unmigrated gathers at different processing stages: as **FF/Chan-sorted raw** data, as **CDP/offset-sorted pre-processed** data ready for application of dynamic corrections, and as **CDP/offset-sorted CRS-processed** data ready for stack and/or migration. The CRS processing (Common Reflection Surface) gives a significant improvement in comparison to the classical CDP processing with NMO (Common Depth Point with Normal MoveOut). In addition, there are also **CDP/offset-sorted image gathers**, either **pre-stack time-migrated** or **pre-stack depth-migrated** available.

The respective file names are self-explaining. All information that is necessary for recording geometry definition should be already present in the headers (source-/receiver-/CDP locations/coordinates/elevations/static corrections, shot/channel numbers, offsets etc.), so it should be easily possible to set up a matching database by extracting them accordingly. The PDF document in the parent folder lists all SGY files again together with additional information.

In the SeismicData/**PostStack** folder there are SGY files with the final results from the reprocessing carried out in 2019/20, they are arranged in subfolders according to the respective poststack processing stage, i.e. **unmigrated**, **post-stack time-migrated**, **pre-stack time-migrated** and **pre-stack depth-migrated**. Each version comes as **raw stack** (nearly true-amplitude), **final stack** (after additional semblance-based amplitude scaling for better readability) and together with the used **velocity model**.

A **Tomographic Inversion** has been conducted, based on the first-break picks of the raw data. This delivers a high-resolution image of the true interval-velocities versus depth down to 3-5 km below surface. The folder contains the derived **VelocityField (1) unmuted** and **(2) muted** to the reliable region, based on the corresponding **NodeCount** result. The tomographic velocities have also partly been used for the final migrations to obtain a better near-surface imaging.

The PDF document in the parent folder lists all SGY files again together with additional information.

4. Graphic Data

The folder **GraphicData** contains graphic representations of the reprocessing results. The sections have been converted from SEGY to color-coded high-resolution PDF which can be displayed or plotted with common software that is able to handle images with 25 000 pixels and more. The images come with top label (showing profile-km and CDP) and with a basic side label (showing profile name and processing version).

The **GraphicData** folder structure is analogous to the **SeismicData** folder. It contains in the subfolders **FinalStacks**, **FinalMigrations** and **Tomography** the respective reprocessed results, sometimes in different versions. There is no graphic representation of unstacked data.

The file names correspond to the seismic data versions and should be therefore self-explaining. The PDF document in the parent folder lists all PDF files again together with additional information.

5. Metadata

In the folder **MetaData** there is accompanying information to the seismic data. The subfolder **SurveyData** contains scans of the original (PRAKLA) field report including appendices as well as the original location maps and the original evaluation of field static corrections. The scans might be overlapping and have not been merged together as they are slightly distorted by the optical scanning procedure from blueprints. Unfortunately, everything is in German language, but they are hopefully of help nevertheless.

In the subfolder **Geometry** there are ASCII tables with all source-/receiver-/CDP-location/-coordinates/-elevation, spread and static information, just in case, that for one or the other file something, e.g. the CDP coordinates, might be missing in the trace headers and have to be externally imported. The tables for **Receivers**, **Sources**, **CDPs**, the **Relation** describing the actually active spread and **Misc** (like additional particulars like static corrections if not included in the other files) are self-explaining by the first comment line in each file. The coordinates are given in the rectangular Gauß-Krüger system (Bessel ellipsoid), the used abbreviations are LOCN (geophone location), SPON (shotpoint order number), SLOC (source location), NSPON (nearest SPON to CDP), NLOC (nearest LOCN to CDP) and VEL (either weathering layer velocity or main refractor velocity in m/s). For import into maps or GIS the CDP line is additionally given in geographic coordinates (Longitude, Latitude, WGS84)

in ASCII and kml format. The PDF document in the parent folder lists all Metadata files again together with additional information.

In **Appendix A** the field parameters and geometry dimensions are compiled in **Table 1** and the general sequence of the reprocessing in **Table 2**.

6. References

Barry, K. M., Cavers, D. A., & Kneale, C. W. (1975). Recommended Standards for Digital Tape Formats. *Geophysics*, 40(2), 344–352. <https://doi.org/10.1190/1.1440530>, https://seg.org/Portals/0/SEG/News and Resources/Technical Standards/seg_y_rev0.pdf

SEG Technical Standards Committee (2002) SEG Y rev 1 Data Exchange format. https://seg.org/Portals/0/SEG/News and Resources/Technical Standards/seg_y_rev1.pdf

Meissner, R. & Bortfield, R.K. (Eds.) (1990). DEKORP-Atlas – Results of Deutsches Kontinentales Reflexionsseismisches Programm. Springer Press.

Stiller M. & Thomas, R. (1989). Processing of reflection-seismic data in the DEKORP Processing Center, Clausthal. In: Emmermann, R. & Wohlenberg, J. (Eds). *The German Continental Deep Drilling Program (KTB)*. Springer Press, pp 177-232. https://doi.org/10.1007/978-3-642-74588-1_9

Stiller, Manfred; Kaerger, Lauretta; Agafonova, Tatiana; Krawczyk, Charlotte; Oncken, Onno; Weber, Michael; Former DEKORP Project Leaders; Former DEKORP Research Group; Former DEKORP Processing Centre (2020): Deep seismic reflection profile DEKORP 1984-2S across the Franconian Platform, South Germany. GFZ Data Services. <https://doi.org/10.5880/GFZ.DEKORP-2S.001>

7. Appendix A

7.1. Table 1: Field parameter summary and geometry dimensions

General information	Recorded	April – May 1984
	by	Prakla-Seismos AG
	for	Geological Survey of Lower Saxony, Germany
	Area	Hesse
	Profile length / direction / azimuth	Reprocessed 74.68 km of total 250.08 km / SE – NW / -50.9029 °
	Total data amount	0.717 GB of total 2.77 GB
Recording	Recording system	Sercel SN 348 / MTA09
	Sample interval	4 ms
	No. of channels	200
	Field filter	Low-cut 8.0 Hz / 18 dB High-cut 62.5 Hz / 72 dB
	Recording format	SEG-B
	Recording time	20 s
Receivers	Geophone type	SM 4 B (10 Hz)
	Geophones per group	24
	Receiver array	In-line array (23 x 3.5 m)
	Group spacing	80 m
	Spread length	16 km
	No. of geophone points	3128 (entire profile)
Sources	Source type	Dynamite Vitesit (max. 30 kg / hole)
	Holes per shotpoint	1
	Source depth	Max. 30 m
	Recording configuration	Off-end shooting (15960 – 40 m – SP)
	Source point spacing	320 m
	No. of source points	684 (entire profile)
CDPs	Coverage (theor. / real)	25- / 22-fold
	CDP-spacing	40 m
	No. of CDPs	1868 (reprocessed part) of 6253 in total
	Final datum	400 m a.s.l.

Geometry dimensions DEKORP 1986-2N

	Record	Location	X coordinate	Y coordinate	Longitude	Latitude
			Gauss-Krueger (Bessel, Potsdam)		Decimal degree (WGS84)	
Source	(1	101	3627789.	5397442.	10.73507475	48.70146086)
	792	3227	3465440.	5582597.	8.51309687	50.37827719
Receiver	(1	101	3627800.	5397400.	10.73521113	48.70108110)
	3128	3228	3465460.	5582675.	8.51337087	50.37897954
CDP	4586	2293	3526137.	5539253.	9.36343229	49.98905291
	6453	3227	3465478.	5582608.	8.51363006	50.37837830

7.2. Table 2: Reprocessing sequence summary

Process	Parameter
Data Output 1	<i>Input data, raw FF-sorted gathers</i>
Geometry Extraction	CDP assignment (Crooked-Line)
Trace Editing	Initial Bad-Trace Elimination
Analytic Gain	Spherical Divergence Correction ($T \cdot v^2$)
First-Break Muting	Offset-dependent
Amplitude Balancing	Surface-consistent, 1 st run
Deconvolution	Surface-consistent spiking (160 ms operator length, 1 % prewhitening, two gates)
Bandpass Filtering	3/8 – 80/100 Hz
Air-Blast Attenuation	Constant fan 333 m/s
Amplitude Balancing	Surface-consistent, 2 nd run with additional bad-trace elimination
Static Correction	to Floating Datum (smoothed receiver elevation)
Velocity Analysis	1 st pass, integrated method
Residual Static Correction	Surface-Consistent, including Iterative Velocity Updates
Velocity Analysis	2 nd pass, integrated method
Noisy Trace Editing	Despiking by Standard Deviation in Supergathers
Ground-Roll Suppression	Cone Window
Data Output 2	<i>Preprocessed CDP-sorted gathers</i>
CRS-Processing	Common Reflection Surface method
Data Output 3	<i>CRS-processed CDP-sorted gathers</i>
Post-NMO/CRS Muting	Exclude refraction residuals
CDP Stacking	with shift to Final Datum (400 m a.s.l.) and Zero-Phase Transformation Coverage: ~22-fold
Coherency Enhancement	Dip attenuation, f-k Filtering, f-x Deconvolution, bandpass Filtering
Data Output 4 a, b, c	<i>CRS Stack (raw) and semblance-scaled for dynamic compression (final) + velocities</i>
Migration	Post-Stack Steep-Dip Finite-Differences Method Input is the CRS Stack
Data Output 5 a, b, c	<i>Post-Stack Time-Migration (raw) and semblance-scaled for dynamic compression (final) + velocities</i>
Migration	Pre-Stack Curved-Ray Kirchhoff Time-Migration (with iterative Velocity Field Update) Input are the unstacked CRS gathers
Post-Migration Muting	Exclude noise residuals
Output 6	<i>Pre-Stack Time-Migrated CDP-sorted image gathers</i>
CDP Stacking	with shift to Final Datum (400 m a.s.l.) and Zero-Phase Transformation Coverage: ~22-fold
Coherency Enhancement	Dip attenuation, f-k Filtering, f-x Deconvolution, Bandpass Filtering
Output 7 a, b, c	<i>Pre-Stack Time-Migration (raw) and semblance-scaled for dynamic compression (final) + velocities</i>
Depth-Model Building	Start model: First-Break Tomo vels + PreSTM vels + GFZ crustal vels Input are the unstacked CRS gathers after Zero-Phase Transformation
Migration	Pre-Stack Isotropic Kirchhoff Depth-Migration (with iterative Velocity Field Update)
Post-Migration Processing	Residual Moveout Correction and Outer Trace Muting
Output 8	<i>Pre-Stack Depth-Migrated CDP-sorted image gathers</i>
CDP Stacking	with shift to Final Datum (400 m a.s.l.) and Zero-Phase Transformation Coverage: ~22-fold
Coherency Enhancement	Dip attenuation, f-k Filtering, f-x Deconvolution, Bandpass filtering (application in time domain)
Output 9 a, b, c	<i>Pre-Stack Depth-Migration (raw) and semblance-scaled for dynamic compression (final) + velocities</i>
Output 10 a, b, c	<i>Tomographic Inversion (unmuted, muted, ray-count)</i> Input are the first-break picks of the raw unstacked data